

DS-2CE56H1T-ITM

5 MP HD EXIR Outdoor Turret Camera

- 1/3" (5 MP) High-Performance CMOS
- HD Analog Output, up to 5 MP Resolution
- 2.8 mm, 3.6 mm, 6 mm fixed focal lens
- True Day/Night
- OSD Menu, DNR, Smart IR
- DWDR
- EXIR Technology, up to 65 ft (20 m) IR Distance
- IP67 Protection
- Up-the-Coax (HIKVISION-C)







Available models:
DS-2CE56H1T-ITM

Hikvision DS-2CE56H1T-ITM EXIR Outdoor Turret Cameras are a versatile solution for all of your security needs. They feature a wide range viewing angle that captures images with a resolution of 5 MP at up to 20 fps. The Turret Camera supports the Hikvision-Up-the-Coax protocol, DWDR, and is equipped with an IR lamp with a range of up to 65 ft (20 m), which facilitates nighttime recording.



| DS-2CE56H1T-ITM | |
|--------------------------|----------------------------------------------------------------------------------------|
| Camera | |
| Image Sensor | 1/3" (5 MP) progressive scan CMOS |
| Effective Pixels | 2592 (H) x 1944 (V) |
| Minimum Illumination | Color: 0.01 lux @ (f/1.2, AGC on), 0 lux with IR |
| Shutter Speed | PAL: 1/25 s to 1/50,000 s NTSC: 1/30 s to 1/50,000 s |
| Lens | 2.8 mm, 3.6 mm, 6 mm fixed focal lens |
| Horizontal Field of View | 86.5° (2.8 mm), 70.1° (3.6 mm), 46° (6 mm) |
| Lens Mount | M12 |
| Day/Night | ICR |
| Angle Adjustment | Pan: 0° to 360°; tilt: 0° to 75°; rotate: 0° to 360° |
| Synchronization | Internal synchronization |
| Video Frame Rate | 2592 x 1944 @ 20 fps |
| HD Video Output | 1 HD-TVI analog output |
| Menu | |
| AGC | Supported |
| D/N Mode | Auto/color/BW (black and white) |
| White Balance | ATW/MWB |
| BLC | Supported |
| WDR | DWDR |
| Language | English, Chinese |
| Functions | Brightness, sharpness, digital noise reduction, mirror, bad pixel correction, smart IR |
| General | |
| Operating Conditions | -40° to 140° F (-40° to 60° C), humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC ±20 % |
| Power Consumption | Maximum 5 W |
| IR Range | Up to 65 ft (20 m) |
| Communication | Up-the-Coax Protocol: HIKVISION-C (HD-TVI output) |
| Dimensions | 3.58" x 3.25" x 2.69" (91 mm x 82.6 mm x 68.3 mm) |
| Weight | 0.77 lbs (approximately 350 g) |

Accessories

| | | | |
|----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
|  <p>PM Vertical Pole Mount</p> |  <p>WML + PC110T Wall Mounting</p> |  <p>CBXS Conduit Base</p> |  <p>DS-1H18 Video Balun</p> |
|  <p>CMPL Horizontal Pole Mount</p> | | | |

Dimensions

