

DS-PHA Series Hybrid Security Control Panel

DS-PHA series hybrid security control panel, containing on-board zones, supports wired/wireless alarm inputs and outputs expanding. It works with Wi-Fi, LAN, GPRS, and 3G/4G communication methods, as well as ISAPI, Ehome 5.0, and DC09 protocol. It is applicable to the scenarios of market, store, house, factory, warehouse, office, etc.



Available Models


- DS-PHA20-P
SAP: 302401397
- DS-PHA20-M
SAP: 302401486
- DS-PHA64-M
SAP: 302401466
- DS-PHA20-W2P: supports Wi-Fi and short video verification
SAP: 302401439
- DS-PHA20-W2M: supports Wi-Fi and short video verification
SAP: 302401487
- DS-PHA64-W4M: supports Wi-Fi and short video verification
SAP: 302401467
- DS-PHA64-W4P: supports Wi-Fi and short video verification
SAP: 302401394
- DS-PHA20-B (PCB only)
SAP: 302401495
- DS-PHA64-B (PCB only)
SAP: 302401497
- DS-PHA20-W2B (PCB only): supports Wi-Fi and short video verification
SAP: 302401499
- DS-PHA64-W4B (PCB only): supports Wi-Fi and short video verification
SAP: 302401501




Features

- Dual path communication of alarm events and other signals over LAN, PSTN, Wi-Fi (-W model), GPRS and 3G/4G utilizing a main and backup channel with configurable priority
- 4/8 on-board wired zones, and expandable with up to 20/64 wired zones
- Up to 16/56 wireless inputs, 18/60 wireless outputs, 8 keyfobs, 1 wired siren and 2 wireless sirens
- Camera accessing (only supported by DS-PHAXX-W2/4)
- Pre-alarm (5 s) and post-alarm (2 s) recording for video verification to the alarm receiving email or mobile client
- Uploads alarm events to alarm receiving center or platform.
- Supports arming/disarming via keypad, mobile client, iVMS-4200, SMS, and tag
- Configuration via web client, Hik-Connect, or iVMS-4200
- Pushes alarm notification via messages and email
- AES-128-bit data encryption
- LED indicator for indicating system status
- Expandable PSTN, 3G/4G, and GPRS interface
- Supports RS-485 input and output expander
- Supports lithium battery (-P model) or storage battery (-M model)
- 1 manufacturer, 1 installer, 1 administrator, and 13 users (DS-PHA20)/45 users (DS-PHA64)

Typical Application





Model		DS-PHA20-P DS-PHA20-M DS-PHA64-M	DS-PHA20-W2M DS-PHA20-W2P DS-PHA64-W4M DS-PHA64-W4P
Device connection	Wireless Detector	Up to 16/56	
	Wireless Output expander	Up to 8	
	Siren	1 wired siren (on-board connection) 2 wireless sirens	
	Keyfob	8	
Alarm input	Partition	4 (DS-PHA20) 8 (DS-PHA64)	
	Zone	4 on-board zones , and 16 wired/wireless zones expandable (DS-PHA20) 8 on-board zones, and 56 wired/wireless zones expandable (DS-PHA64)	
Alarm output	Alarm output	2 on-board outputs, and 18 wired/wireless outputs expandable (DS-PHA20) 4 on-board outputs, and 60 wired/wireless outputs expandable (DS-PHA64)	
Function	Scheduled output control	Supported	
	Scheduled arming/disarming	Supported	
	SMS notification (with 3G/4G/GPRS module)	Supports up to 8 mobile phone numbers	
	Network camera accessing	N/A	2 (DS-PHA20) 4 (DS-PHA64)
Application & Protocol	Application	iVMS-4200 (client software) Hik-Connect (mobile client)	
	Protocol	ISAPI: Supports client software and web client Cloud P2P: Supports cloud P2P privacy protocol DC09: ARC accessible (CID/SIA)	
Network	Wired network	10M/100M Ethernet	
	Cellular Network (with 3G/4G/GPRS module)	Supports report push-notification to ARC & Cloud	
Wi-Fi	Standard	N/A	802.11b/g/n
	Encryption	N/A	64/128-bit WEP,WPA/WPA2,WPA-PSK/WPA2-PSK,WPS
	Configuration	N/A	AP Mode
	Distance	N/A	Indoor: ≤ 50 m Outdoor: ≤ 100 m
Interface & Component	TAMPER Switch	1, front cover tamper-proof	
	Network Interface	1, RJ45 10M/100M Ethernet Interface	
	Telephone Interface	1, PSTN expander interface	

Model		DS-PHA20-P DS-PHA20-M DS-PHA64-M	DS-PHA20-W2M DS-PHA20-W2P DS-PHA64-W4M DS-PHA64-W4P
	RS-485 Terminal	1, extended up to 20 inputs/outputs (with RS-485 module), and 9 wired keypads extendable (DS-PHA20) 1, extended up to 64 inputs/outputs (with RS-485 module), and 9 wired keypads extendable (DS-PHA64)	
	Siren Power Interface	1, 12V	
	Battery Interface	Lithium battery (-P model) Storage battery (-M model)	
User	User	Installer: 1 Administrator: 1 Manufacturer:1 Operator: 13 (DS-PHA20), 45 (DS-PHA64)	
Others	Power	100 to 240 VAC, 50/60 HZ	
	Current	3 A Max	
	Operation Temperature	-10 °C to 55 °C (-4 °F to +122 °F)	
	Operation Humidity	10% to 90% (No condensing)	
	Dimension (W × H × D)	Plastic Case: 220 mm (8.6") × 152 mm (6.0") × 31.5 mm(1.2") Metal Case: 351.4 mm (13.8") × 261.4 mm (10.3") × 93.3 mm (3.7")	

Distributed by



HIKVISION

Headquarters

No.555 Dianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-885-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28489900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27(10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-460
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.porfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
sales.me@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-57-99
saleru@hikvision.com

Hikvision Korea
T +82-10111-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933758
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com